

646 PLUS SATIN/ LOW GLOSS

WATER BASE SEALER - FINISH

- * oil resistant
- * self-crosslinking
- * for high traffic
- * water resistant
- * stain resistant
- * indoor/ outdoor

MADE IN THE U.S.A.

SPECIFICATIONS: Milky white when applied, but dries clear.

FINISH: Semi-gloss

CLEAN-UP: Soap and water.

VOC: < 100 grams/liter

FLASH POINT: ABOVE 175 degrees.

SHELF LIFE: Two years minimum

when stored at room temperature, and unopened.

DESCRIPTION: **SATIN 646 PLUS** is a Self-Crosslinking Acrylic /Polyurethane low V.O.C. Sealer that has great chemical resistance, early water-resistance, and good hot tire resistance. **646** gives plastic film forming protection and color enhancement while maintaining a beautiful, natural satin look. **SATIN 646 PLUS** is below 100 V.O.C., meeting SoCal A.Q.M.D. requirements. **Satin 646 Plus** is a water based, breathable sealer that performs like an oil based lacquer. **This product makes oil based lacquer obsolete. Use 646 PLUS in areas where hydrostatic pressure exists.** **646 PLUS** meets, or beats the performance of competitive products in protection and hardness. It is easy to use, without overwhelming, harmful or heavy odors.

USES: Use on bricks, pavers, concrete, unglazed tile, slate, stone, clay, rock and other porous products. This water based self-crosslinking semi-gloss sealer is the best plastic film forming semi-gloss sealer on the market for indoor, and outdoor.

DIRECTIONS: Test **SATIN 646 PLUS** first on an uninstalled piece of stone. Apply **646PLUS** with a brush, sprayer, roller, or sponge mop. Work the first coat into tiles for deep penetration. When visibly dry; apply a light second coat. If the surface darkens or appears wet, it is not yet sealed and needs another coat. Tiles are completely sealed when further coating does not darken or give a wet appearance.
NEVER APPLY ANY SEALER TO A SURFACE UNLESS IT IS COMPLETELY DRY!

COVERAGE: One gallon of **646 PLUS SATIN/ LOW GLOSS** will cover approximately 150 to 250 square feet, depending on how porous the surface is.

LIMITS: Do not use below 45 . Do not let **646 PLUS**

puddle or run down vertical surfaces. When testing for desired results be sure to allow 72 hours for curing.

CAUTION: Use rubber gloves when applying. Avoid contact with skin. Prolonged exposure to vapors may be harmful or fatal. Use in a well ventilated area. In conditions which do not permit good ventilation; use of a breathing apparatus is recommended.

NOTICE: Our only obligation shall be to refund purchase price or replace any of our product proved to be defective. Beyond the purchase price of materials supplied by us, we assume no liability for damages of any kind and the user accepts the product "as is" and without warranties either expressed or implied. The suitability of the product for an intended use shall be solely up to the user.

SHIPPING: Class 55 for water based paint and related products.

Packaging: 12 quarts to a case, 4 gallons to a case and 5 gallon pails.

STORE ABOVE 40 F DO NOT FREEZE

Product of: Duro Shine Sealers
P.O. Box 5358
North Hollywood, Cal. 91606

818 982-6412
818 982-8662 fax

www.duroshine.com